



TOWN OF ANDOVER

Town Offices
36 Bartlet Street
Andover, MA 01810
(978) 623-8640
www.andoverma.gov

ANDOVER BOARD OF HEALTH SEWER REGULATIONS FACT SHEET DRAIN LAYER SPECIAL INFORMATION (Draft 1/28/09)

- All trenches with piping must have **metallic trace tape** laid above the pipe prior to backfilling.
- **Backwater Valves** are required to be installed in all building sewers, 10' from the foundation.
- If a pump is required to bring wastewater to the municipal sewer, an engineered plan is required.
- When one part of a property or facility is connected to sewer, the entire facility or all facilities on the property must be connected to sewer. Gray water or septic systems will not be allowed to remain in use.
- You must be up to date with all permits issued in your name. If you owe us as-builts or certifications, we reserve the right to withhold new permits until the late paperwork is submitted.
- In general, all as-builts and certifications are due within **30 days** of your final inspection.
- **Do not begin work without your permits in hand**; if you do so, you risk financial penalties and possible loss of your Andover Licenses.
- Building sewers must be laid with a **minimum** slope of 2%.
- Trench permits are required as part of sewer construction or connection. One permit per job is required and can be obtained in conjunction with a Building Sewer Installation Permit, or a Street Opening Permit.

DISCLAIMER: This Fact Sheet is for general informational purposes and guidance only. If any statements conflict with the actual regulations, the regulations shall prevail. It is the applicant or user's responsibility to consult the regulations for full text and applicability.